



MV OLV SUPPORTER



PRINCIPAL PARTICULARS

Port Of Registry	Port Kelang
Call Sign	9MFE9
Official No.	332385
Year Built	2006
Class	Bureau Veritas
Notation	Class 1 * Hull * MACH, Tug, Unrestricted Navigation
Type	Utility Vessel
Class No.	10371A
IMO No.	9431329
Hull No.	LS 146
Flag	Malaysia
Owner	AME Subsea Management Sdn. Bhd.
Operator	AME Subsea Management Sdn. Bhd.

DIMENSION

Length Overall	48.00 m
Length Waterline	46.43 m
Length Between	
Perpendicular	42.40 m
Breadth Moulded	11.80 m
Depth Moulded	4.60 m
Draft Moulded	3.80 m
GRT	675 MT
NRT	202 MT
Deadweight	673.48 MT @ 3.8 m
Air Draught	17m

PERFORMANCE

Maximum Speed	12.5 Knots @ 15.5 MT / 24 hr
Economical Speed	10.0 Knots @ 12.3 MT / 24 hr
Type of fuel	Marine Gas Oil

CARGO CAPACITIES

Deck Strength	4 MT/ m ²
Clear Deck Area	168.75 m ²
Fuel Oil	560 m ³
Fresh Water	180 m ³
Freezer/Chiller	3 m ³ / 3 m ³
Foam	10 m ³
Detergent	10 m ³

PROPULSION SYSTEM

Main Engine	2 x Caterpillar 3512B @ 1750 BHP
Main Generator	3 x Caterpillar 3406 @ 245 kW
Bow Thruster	1 x 5 MT
Steering Gear	electro-hydraulic type with twin screw arrangement
Propulsion	2 x FPP Type with Kort Nozzle
Rudders	2 x Conventional Rudder

DECK EQUIPMENT

Windlass	1 x electro-hyd for Ø 28 mm rated 5 MT @ 12 m/ min 1 st layer
Anchor	1020 kg [Port] & 792 kg [Stbd] Stockless Bower Anchor
Anchor Chain	520 m x 28 mm Ø, port & stbd
Capstan	1 x 5 MT

NAVIGATIONAL /COMMUNICATION

GMDSS	3 x NSR
SSB	1 x Samyung
GPS Navigator	1 x Matsutec
SART	1 x Jotron & 1 x CY
Inmarsat C	1 x NSR
Satellite EPIRB VHF Radio	1 x NSR & 1 x JRC
Portable VHF Radio	4 x Motorola
Navtec Receiver	1 x NSR
X-Band Radar	1 x JRC
Echo Sounder	1 x Ninglu
Anemometer	1 x Marinelite
Gyrocompass	1 x Yokogawa
Autopilot	1 x Com Nav 2001
Weather Fax	1 x JRC
Speed Log	1 x JRC
Magnetic Compass	1 x Saura Keiki
Joystick	Kongsberg C Joy
Automatic Identification System	1 x JRC JHS-182

Disclaimer: This brochure is for promotional purposes only. All details are provided in good faith but without guarantee; Specifications are subject to change without notice and do not constitute an offer or contract. Interested parties are advised to verify all information through direct inspection of the vessel.
Last revised: May 2026



MV

OLV SUPPORTER



ACCOMMODATIONS

Berths	2 x 1 berth cabin = 2
	1 x 2 berth cabin = 2
	6 x 4 berth cabins = 24
Total	28
All cabins are fully air-conditioned	

LIFE SAVING APPLIANCE

Search Lights	2 x 1500 W
Floodlights	6 x 500 kW
Liferafts	6 x 15 men
Lifebuoys	8 pcs with buoy lights
Life jackets	23 x Synthetic type
Parachute Distress	
Signal	12 pcs
Rescue Boat	1 x 6 men rigid c/w 25 hp motor and david launching

TOWING EQUIPMENT

Stern Roller	1.45 m Ø and 3.5 m length w/ SWL 200 MT
--------------	---

DISCHARGE RATES

Fuel Oil	1 x 50 m ³ / hr @ 50 m head
Fresh Water	1 x 50 m ³ / hr @ 50 m head

FIRE FIGHTING EQUIPMENT

External

FiFi	Class 1/2
Fire pump	1 x 1200 m ³ / hr at 14 bar
Fire monitor	2 x 600 m ³ / hr at 12 bar inlet pressure

Internal

Fixed System in E/R	CO2 system in engine room
Fire Detection System	All living space and Engine Room

OTHERS

Rescue Zone	Port & Stbd Side
Sewage Treatment Plan	1 x 36 men



Scan to connect with us